

DuploCOLL® 377

Art. No. 11 00 73

Double-sided, transparent, distortion-free adhesive mounting tape

Product construction			
	Name	Colour	Thickness [mm]
Liner	Polypropylene film	red	approx. 0,08
Adhesive covered side	Modified acrylic		
Carrier	Polyester film	transparent	approx. 0,20
Adhesive open side	Modified acrylic		
Total thickness:			approx. 0,28

Product advantages

- Good initial and final adhesion
- High shear strength
- Good ageing resistance
- Extensive resistance to the influence of chemicals (domestic cleaning material and polishing agents)

Main application fields

- Making plastics, signs, face plates and scales in the electrical and electronic industries self-adhesive
- Self-adhesive, distortion-free preparation of rubber goods (mouldings, profiles)

Product features		Applicability on	
Initial adhesion	● ● ●	Foam	○ ○ ○
Final adhesion	● ● ○	Rubber	● ● ○
Dimensional stability	● ● ●	Fabric	● ● ●
Adhesion on even surfaces	● ● ●	Glass/Ceramics	● ● ●
Adhesion on rough surfaces	● ● ●	Wood	● ● ●
Ageing resistance	● ● ○	High energy plastics: PVC, PC, ABS,...	● ● ●
Weathering resistance	● ● ○	Low energy plastics: PE, PP,...	● ● ○
Chemical resistance	● ● ○	Metal	● ● ●
Resistance to plasticizers	● ● ●	Paper/Cardboard	● ● ●
● ● ● very suitable ● ● ○ suitable ● ○ ○ suitable with reductions ○ ○ ○ not suitable			

Specific technical data*

Temperature range -40 °C to +120 °C

* Specific test results, statistically not approved.


DuploCOLL® 377

Art. No. 11 00 73

Double-sided, transparent, distortion-free adhesive mounting tape

Technical Data

Shear strength	on steel according to DIN EN 1943, edition 1996, at +23 °C +/- 2°C	60 N/625 mm ²
Peel strength	on steel according to DIN EN 1939, edition 1996, at +23 °C +/- 2°C	35 N/25 mm



Application

Recommended application temperature 18 °C to 35 °C

Application guidelines www.lohmann-tapes.com

Storage

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).

The storage stability is one year after delivery.

Product presentation

Converted product	Rolls				
Width [mm]	> 6	> 12			
Length [m]	50	100/200			
Max. log width: 1260 mm	Other dimensions, die-cuts and sheets on request.				

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

IMPORTANT NOTE

The physical characteristics contained in this data sheet represent typical or average values. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. Many factors beyond our control and uniquely within buyer's knowledge and control can affect the use and performance of our tape in a particular application. EXCEPT AS EXPRESSIVELY AGREED IN WRITING WE DO NOT TAKE OVER ANY WARRANTY OR LIABILITY FOR THE SUITABILITY OR USABILITY OF OUR TAPES FOR CERTAIN PURPOSES AND APPLICATIONS RESULTING FROM BUYER'S SPECIAL USAGE OF THE TAPES. EXCEPT WHERE PROVIDED BY MANDATORY LEGAL PROVISIONS, WE WILL NOT BE LIABLE FOR ANY DIRECT OR INDIRECT MATERIAL OR IMMATERIAL LOSSES OR DAMAGES ARISING FROM THE USAGE OR APPLICATION OF OUR TAPES. Solely the buyer is responsible for determining the suitability of the specific tape for its use in connection with his method of application. Please consult our Technical Applications Department for specific advice.

Date of issue: October 2016

Lohmann GmbH & Co. KG
 Irlicher Strasse 55
 56567 Neuwied
 Germany
 Phone: + 49 (0) 26 31 34 - 0
 Fax: + 49 (0) 26 31 34 - 6661
 E-mail: info@lohmann-tapes.com

For further information
www.lohmann-tapes.com

