

# DuploCOLL® 91111.1 NP

Double-sided adhesive foam tape with a special developed high performance adhesive for new paint systems

Product construction			
	Name	Colour	Thickness [mm]
Liner	Polyethylene film	yellow	approx. 0,10
Adhesive covered side	High performance adhesive		
Carrier	Polyethylene foam	black	approx. 1,10
Adhesive open side	High performance adhesive		
			<b>Total thickness:</b> approx. 1,20

## Product advantages

- The specially developed high performance adhesive is characterized by an excellent final adhesion, also on dirt-repellent and scratch-proof coating systems and outstanding shear strength.
- The adhesive shows consistent results after established ageing tests in the automotive industry (heat, humidity, cold, etc.).
- DuploCOLL® NP with its compressible foam carrier is better in compensating component tolerances than hard foamed systems.

## Main application fields

- Permanent bonding of exterior parts, e.g. trim parts, door covers, wheel house covers, door sill panels or moldings, emblems and letterings

## Specific technical data\*


Temperature range -40 °C to +100 °C

# DuploCOLL® 91111.1 NP

Double-sided adhesive foam tape with a special developed high performance adhesive for new paint systems

## Technical Data

<b>Shear strength</b>	on steel according to DIN EN 1943, edition 1996, at +23 °C +/- 2°C	120 N/625 mm <sup>2</sup>
<b>Peel strength</b>	on steel according to DIN EN 1939, edition 1996, at +23 °C +/- 2°C	≥ 40 N/25 mm



## Application

<b>Recommended application temperature</b>	18 °C to 35 °C
<b>Application guidelines</b>	<a href="http://www.lohmann-tapes.com">www.lohmann-tapes.com</a>

## Storage

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).  
The storage stability is one year after delivery.

## Product presentation

Converted product	Rolls	Spools
<b>Width [mm]</b>		
<b>Length [m]</b>		
<b>Max. log width: 1260 mm</b>	on request	

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

## IMPORTANT NOTE

The physical characteristics contained in this data sheet represent typical or average values. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. Many factors beyond our control and uniquely within buyer's knowledge and control can affect the use and performance of our tape in a particular application. EXCEPT AS EXPRESSIVELY AGREED IN WRITING WE DO NOT TAKE OVER ANY WARRANTY OR LIABILITY FOR THE SUITABILITY OR USABILITY OF OUR TAPES FOR CERTAIN PURPOSES AND APPLICATIONS RESULTING FROM BUYER'S SPECIAL USAGE OF THE TAPES. EXCEPT WHERE PROVIDED BY MANDATORY LEGAL PROVISIONS, WE WILL NOT BE LIABLE FOR ANY DIRECT OR INDIRECT MATERIAL OR IMMATERIAL LOSSES OR DAMAGES ARISING FROM THE USAGE OR APPLICATION OF OUR TAPES. Solely the buyer is responsible for determining the suitability of the specific tape for its use in connection with his method of application. Please consult our Technical Applications Department for specific advice.

Date of issue: September 2019

Lohmann GmbH & Co. KG  
Irlicher Strasse 55  
56567 Neuwied  
Germany  
Phone: + 49 (0) 26 31 34 - 0  
Fax: + 49 (0) 26 31 34 - 6661  
E-mail: [info@lohmann-tapes.com](mailto:info@lohmann-tapes.com)

For further information  
[www.lohmann-tapes.com](http://www.lohmann-tapes.com)

 **Lohmann**  
The Bonding Engineers