

For the preparation of a preliminary data sheet, there are not yet enough measured values and/or production runs to determine statistically validated average/limit values. In individual cases, the repeatability in terms of production technology is not yet ensured.

DuploCOLL® VTR 150

Single sided non-woven tape with doted adhesive coating

Product construction			
	Name	Colour	Thickness [mm]
Liner	Silicone Paper	white	approx. 0,08
Adhesive	Synthetic rubber, partial doted		approx. 0,10
Carrier	Non-woven	white	approx. 0,70
Total thickness:			approx. 0,88

Product advantages

- Good permeability to air
- Stop function to most usual foaming agents
- Perforation for easy usage

Main application fields

- Ventilation tape for closing of exhaust holes during foaming process of refrigerators.

Specific technical data carrier*

Area weight:	ca. 150 g/m ²
Strength:	350 N/5cm md 200 N/5 cm cd
Elongation:	45 % md 55% cd
Permeability to air:	280l/m ² s
Pore size:	45 µm (bubble point) 25 µm (mean flow)
Volume of pores:	76 %

* Specific test results, statistically not approved.

DuploCOLL® VTR 150

Single sided non-woven tape with dotted adhesive coating

Application

Recommended application temperature 18 °C to 35 °C

Application guidelines www.lohmann-tapes.com

Storage

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).

The storage stability is 1 year after delivery. Protect product from direct sunlight and humidity.

Product presentation

Dimensions, die-cuts and sheets on request.

For mechanical mounting of this adhesive tape we also offer a wide range of application devices.

IMPORTANT NOTE

The physical characteristics contained in this data sheet represent typical or average values. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. Many factors beyond our control and uniquely within buyer's knowledge and control can affect the use and performance of our tape in a particular application. EXCEPT AS EXPRESSIVELY AGREED IN WRITING WE DO NOT TAKE OVER ANY WARRANTY OR LIABILITY FOR THE SUITABILITY OR USABILITY OF OUR TAPES FOR CERTAIN PURPOSES AND APPLICATIONS RESULTING FROM BUYER'S SPECIAL USAGE OF THE TAPES. EXCEPT WHERE PROVIDED BY MANDATORY LEGAL PROVISIONS, WE WILL NOT BE LIABLE FOR ANY DIRECT OR INDIRECT MATERIAL OR IMMATERIAL LOSSES OR DAMAGES ARISING FROM THE USAGE OR APPLICATION OF OUR TAPES. Solely the buyer is responsible for determining the suitability of the specific tape for its use in connection with his method of application. Please consult our Technical Applications Department for specific advice.

Date of issue: November 2016