

# DuploMED® 22260



Diagnostic



Electrodes



Wound Care



Surgical



Ostomy



Consumer Healthcare



Wearables



## Product construction

	Name	Colour	Thickness (mm)
Liner	PET film	transparent	approx. 0,050
Adhesive closed side	Medical grade acrylate	transparent	approx. 0,450
Carrier	Polyethylene foam	beige	
		<b>Total thickness</b>	approx. 0,500

## Main application fields

- Closure systems for ostomy bags
- Applications requiring top cushioning
- Attachment of medical devices to skin

## Product advantages / Features and Benefits

- Excellent Conformability
- Good adhesion to skin
- Good adhesion to plastic components
- Easy liner release to enable automated production processes

## Standard technical data

Peel strength *	90 °; substrate POM, at +23 °C ± 2°C	9	N/25 mm
Elongation	according to DIN EN 29073-3 MD	260	%
	according to DIN EN 29073-3 CD	440	%
Tensile strength	according to DIN EN 29073-3 MD	13	N/15 mm
	according to DIN EN 29073-3 CD	9	N/15 mm
Peel strength 180°	on stainless steel at +23 °C ± 2°C	35	N/25 mm

## Technical data foam

Material	Polyethylene foam
Color	tan
Density (acc. ISO-845)	95 kg/m <sup>3</sup>

\* Test results are statistically approved.

# DuploMED® 22260

## Biocompatibility and safety

Customers should perform their own assessment to ensure the final product is in compliance with all applicable Medical Device regulatory requirements. To support the assessment, and upon request, Lohmann can provide, where available, biocompatibility testing results (ISO10993) specific to either the product supplied by Lohmann or its' constituent components.

## Application condition

Recommended application temperature	18 °C to 35 °C
Application guidelines	<a href="http://www.lohmann-tapes.com">www.lohmann-tapes.com</a>

## Storage and shelf-life

Adhesive tapes should be stored at room temperature and normal humidity (50-70 %).  
When properly stored the shelf-life of the product is at least 2 years after delivery.

## Product presentation

Converted product	Rolls	Spools
Width [mm]		
Length [m]		
Max. log width:	1260 mm	Other dimensions, die-cuts and sheets on request.



## IMPORTANT NOTE

The physical characteristics contained in this data sheet represent typical or average values. All application related statements, information and recommendations herein are given to the best of our knowledge and practical experience. Many factors beyond our control and uniquely within buyer's knowledge and control can affect the use and performance of our tape in a particular application. EXCEPT AS EXPRESSIVELY AGREED IN WRITING WE DO NOT TAKE OVER ANY WARRANTY OR LIABILITY FOR THE SUITABILITY OR USABILITY OF OUR TAPES FOR CERTAIN PURPOSES AND APPLICATIONS RESULTING FROM BUYER'S SPECIAL USAGE OF THE TAPES. EXCEPT WHERE PROVIDED BY MANDATORY LEGAL PROVISIONS, WE WILL NOT BE LIABLE FOR ANY DIRECT OR INDIRECT MATERIAL OR IMMATERIAL LOSSES OR DAMAGES ARISING FROM THE USAGE OR APPLICATION OF OUR TAPES. Solely the buyer is responsible for determining the suitability of the specific tape for its use in connection with his method of application. Please consult our Technical Applications Department for specific advice.

Date of issue: March 2023